

MEGA GREEN™ ST (SOILTIGHT) IB PIPE

Now the strength you need is good for the environment

Our new MEGA GREEN ST IB pipe offers significant performance advantages over reinforced concrete and corrugated metal pipe. Plus, it has the best soil-tight joint in the industry. Better yet, it's green. MEGA GREEN pipe has a minimum recycled content of 40%. You can feel better knowing that you are using a product that is actually good for the environment. Available in diameters from 12" to 60" (300 to 1500mm).

Hancor MEGA GREEN ST IB pipe contains a superior built-in bell-and-spigot joint. The joints are sealed by high-quality, factory-installed rubber gaskets that meet all the requirements of ASTM F477. Flared bell-and-spigot significantly improve ease of installation.

APPLICATIONS:

Storm Sewers	Retention/Detention
Mining/Forestry/Industrial	Waterways
Golf, Turf & Recreation	Grain Aeration
Land Reclamation	Ditch Enclosures

FEATURES:


- 12" – 60" (300 to 1500 mm) diameters available
- 6m (19 ft, 8 in) length available
- Bell and spigot joint design
- In-line bell design
- Exceptional joint strength
- Excellent abrasion and corrosion resistance
- Light weight
- Fast installation times
- Structural strength that will support H-25 live loads with 12" (300mm) minimum cover (60" pipe requires 2' cover for H-25 loads)

Hancor Service: Hancor representatives are committed to providing you with the answers to all your questions, including specifications, installation and more.



BENEFITS:

- Variety of diameters that will fit in any project
- Unlike pipes from other manufacturers, joint only requires lube for fitting – ends are pushed together for easy field installation
- Installation cost savings from lower shipping costs, fewer people, and less heavy equipment required
- The reinforced polyethylene bell minimizes distortion Chipping and cracking common to concrete pipe bells, is eliminated
- Hydraulic efficiency from smooth interior



HANCOR MEGA GREEN ST IB PIPE SPECIFICATIONS

SCOPE

This specification describes 12- through 60-inch (300 to 1500 mm) Hancor MEGA GREEN ST IB pipe for use in gravity-flow drainage applications.

PIPE REQUIREMENTS

MEGA GREEN ST IB pipe shall have a smooth interior and annular exterior corrugations.

- 12- through 60-inch (300 to 1500 mm) shall meet ASTM F2648.
- Manning’s “n” value for use in design shall be 0.012.

JOINT PERFORMANCE

Pipe shall be joined using a bell & spigot joint meeting ASTM F2648. The joint shall be soil-tight and gaskets, when applicable, shall meet the requirements of ASTM F477. Gaskets shall be installed by the pipe manufacturer and covered with a removable wrap to ensure the gasket is free from debris. A joint lubricant supplied by the manufacturer shall be used on the gasket and bell during assembly.

FITTINGS

Fittings shall conform to ASTM F2306. Bell and spigot connections shall utilize a spun-on or welded bell and valley or saddle gasket meeting the soil-tight joint performance requirements of ASTM F2306.

MATERIAL PROPERTIES

The PE compound used for pipe production shall be high density polyethylene conforming with the minimum requirements of cell classification 435420C, as defined and described in the latest version of ASTM D3350, except that carbon black content shall not exceed 4%. The design engineer shall verify compatibility with overall system including structural, hydraulic and installation requirements for the given application.

INSTALLATION



Installation shall be in accordance with ASTM D2321 and Hancor published installation guidelines with the exception that minimum cover in trafficked areas for 12- through 48-inch (300 to 1200 mm) diameters shall be one foot (0.3 m) and for 60-inch (1500 mm) diameters shall be 2 ft (0.6 m) in single run applications. Maximum fill height as measured from the top of the pipe to the top of the pavement shall be 8 feet. Contact your local Hancor representative or visit our website at www.hancor.com for a copy of the latest installation guidelines.

PIPE DIMENSIONS

Pipe I.D., in. (mm)	Nominal Diameter, in (mm)								
	12 (300)	15 (375)	18 (450)	24 (600)	30 (750)	36 (900)	42 (1050)	48 (1200)	60 (1500)
Pipe O.D.*, in. (mm)	14.5 (368)	18 (457)	21 (533)	28 (711)	36 (914)	42 (1067)	48 (1219)	54 (1372)	67 (1702)
Perforations	All diameters available with or without perforations.								

*Pipe O.D. values are provided for reference purposes only, values stated for 12- through 60-inch are ± 1 inch. Contact a sales representative for exact values.

- Check with sales representative for availability by region.



DIRECT CONTACT

Customer Service
888-FOR PIPE (367-7473)
Fax 888-FAX PIPE (329-7473) 24 hours a day

ELECTRONIC MEDIA

Web Site
Find market- and application-specific information and the latest industry news at our ON-Line Pipeline – www.hancor.com

Hancor “Terms and Conditions of Sale” are available on the Hancor website, www.hancor.com